

OPEN SKID OR CANOPY · PRIME / STANDBY · 50 & 60 Hz

WEICHAI / WUXI POWER

潍柴 · 无锡动力 静音型柴油发电机组

The WD series is the heavy end of the Chinese engine market: high displacement, low stress per litre, built for continuous duty on mines, quarries and processing plants.

259 – 900 kW · 325 – 1 130 kVA



MODEL RANGE · DIMENSIONS & WEIGHT

Genset model	Engine	Prime kW	Stdby kW	≈ kVA	Cyl · bore × stroke	Disp L	Fuel g/kWh	Oil g/kWh	Canopy L×W×H mm	Weight kg
KTZ230WD	WD129TAD23	259	—	324	6-135×150	12.9	<198	<0.67	2750×1200×1800	2400
KTZ250WD	WD129TAD25	284	—	355	6-135×150	12.9	<198	<0.67	2800×1200×1800	2550
KTZ280WD	WD135TAD28	308	—	385	6-138×150	13.5	<198	<0.67	2900×1200×1800	2600
KTZ300WD	WD145TAD30	340	—	425	6-138×160	14.5	<198	<0.48	3000×1200×1800	2650
KTZ330WD	WD145TAD33	373	—	466	6-138×160	14.5	<198	<0.48	3000×1200×1800	2650
KTZ350WD	WD145TAD35	388	—	485	6-138×160	14.5	<198	<0.48	3100×1200×1800	2700
KTZ380WD	WD269TAD38	420	—	525	12-138×150	26.9	<198	<0.67	3300×1350×1800	3300
KTZ400WD	WD269TAD41	460	—	575	12-138×150	26.9	<198	<0.67	3300×1350×1800	3400
KTZ430WD	WD269TAD43	475	—	594	12-138×150	26.9	<198	<0.67	3400×1400×2000	3800
KTZ450WD	WD269TAD45	512	—	640	12-138×150	26.9	<198	<0.67	3400×1400×2000	3800
KTZ480WD	WD269TAD48	530	—	662	12-138×150	26.9	<198	<0.67	3400×1400×2000	3850
KTZ500WD	—	556	—	695	12-138×150	26.9	<198	<0.67	3400×1400×2000	3900
KTZ560WD	WD269TAD56	618	—	772	12-138×150	26.9	<198	<0.67	3450×1450×2100	4000
KTZ580WD	WD287TAD58	646	—	808	12-138×160	28.7	<198	<0.67	3450×1450×2100	4050
KTZ600WD	WD287TAD61	680	—	850	12-138×160	28.7	<198	<0.67	3450×1450×2100	4250
KTZ680WD	WX287TAD68	750	—	938	12-145×165	32.7	<196	<0.48	3450×1450×2100	5500
KTZ680WD	WD327TAD68	750	—	938	12-145×165	32.7	<196	<0.48	3450×1450×2100	5500
KTZ750WD	WD327TAD78	858	—	1072	12-145×165	32.7	<196	<0.48	3500×1500×2200	5600
KTZ800WD	WD327TAD82	902	—	1128	12-145×165	32.7	<196	<0.48	3500×1500×2200	5800

Prime kW = continuous rating. Standby kW = limited-hour rating. ≈ kVA is derived at power factor 0.8 and is given for reference — we quote in kW; please confirm which unit your specification uses. Dimensions and weight refer to the sound-attenuated canopy version; open skid sets are smaller and lighter. Up to 1 000 kVA, three sets load into one 40HQ container. Other engine makes available on request.